


**COMPRESSED CYLINDER
SERVICES**

Customer Service
T: (800) 610-4571
F: (800) 610-4571
 customerservice@compcylserv.com
 www.compcylserv.com



Deployment Now? 24/7 Dial X119



R-134A Refrigerant
1,1,1,2- Tetrafluoroethane


Shipping Name: 1,1,1,2- Tetrafluoroethane
 UN3159
 Hazard Class: 2.2 (Non-Flammable Gas)
 CAS: 811-97-2
 ERG: 126



**e-Gas
CLICK HERE**




Synonyms: Dymel 134a, Genetron 134a, HFA-134a, HFC-134a, R-134a, Suva 134a, Norflurane
ODP: 0 / GWP: 1700
Replaced/ Phased-Out : CFC-12 Dichlorodifluoromethane
Alternative Refrigerant: HFO-1234YF
Related Refrigerants: HFC-32 Difluoromethane, HFC-125 Pentafluoroethane
Recommended Lubricant: POE Polyolester Oil



Valve Types

DOT 4BW300 Refillable Cylinders
 Dual Port/ Dual Valve Vapor & Liquid
 NSN: 8120-01-204-0182
 Connection: CGA-660



DOT 39 Non-Refillable Cylinders
 HVAC Connection: CGA-167
 Automotive Connection: CGA-165
 (Not Shown)

FEDSPEC Primary Color 12246
MIL-STD-101B & FED-STD-595

Commercial, HVAC, Automotive
AHRI (2012) N PMS 2975


CLICK HERE FOR MSDS

PURITY IS A PROBLEM! CERTIFIED PRODUCT ONLY: US NAVY FLEET USE COMPCYLSERV


Problem solved with COMPCYLSERV: we are one of only three companies globally whom can provide certified R-134A to AHRI-700 (2011) Specifications & Military Standards. Among other requirements, the AHRI-2011 specification requires Halogenated Unsaturated Volatile Impurities <40ppm PPM By Weight, an unmatched industry challenge that has plagued manufacturers, suppliers & the Fleet. Knowledge is power. We provide a COA Certificate of Analysis from an independent EPA-Certified Facility with each cylinder at no additional charge. Product that does not meet the AHRI-700 (2011) specifications negates manufacturer liability/ warranty. Bad product also costs the Warfighter... Furthermore in large volumes Halogenated Unsaturated Compound Impurities can cause internal corrosion. There have also been traces of R-40 (Methyl Chloride or Chloromethane) identified in various refrigerants which is extremely toxic, flammable & highly reactive when exposed to aluminum. Know your product before installing aboard your centrifugal air conditioning unit.

CYLINDER SIZES

Cylinders shown are provided for reference only, all cylinders shall comply to color specifications as stated in MIL-STD-101B.



MIL-STD-147E Palletization Available Upon Request



Type	Content Capacity	Content NSN	Cylinder NSN	DOT	Tare Weight	Outlet	Cylinder Exchange Price <i>Includes COA</i>	Cylinder Price <i>Content Sold Separately</i>
<i>Product Identification Number</i> IAW CID A-A-58060								
AA58060-R134AW9.071847	20LB	6830-01-555-8678	8120-01-561-9035	4BA/W300	18LB	CGA-660	\$245.00	\$180.00
AA58060-R134AW13.6	30LB	6830-01-390-9622	N/A	39 (Disposal)	6LB	CGA-167	\$205.00	N/A
AA58060-R134AW13.6	30LB	6830-01-412-6362	N/A	39 (Disposal)	6LB	CGA-165	\$205.00	N/A
AA58060-R134AW19.4	43LB	6830-01-370-6207	8120-01-370-8189	4BA/W300	23LB	CGA-660	\$398.25	\$185.00
AA58060-R134AW57	125LB (12"x36")	6830-01-370-8756	8120-01-370-8190	4BA/W300	63LB	CGA-660	\$971.50	\$225.00
AA58060-R134AW57	125LB (10"x49")	6830-01-527-8354	8120-01-527-8290	4BA/W300	48LB	CGA-660	\$971.50	\$225.00
AA58060-R134AW454	1000LB	N/A	N/A	4BW300	335LB	CGA-660	\$5,750.00	\$2,000.00

Pricing subject to change without notice, based on market volatility.



DLA Cylinder Specifications

The Defense Logistics Agency adheres to stringent specifications in order to provide Logistics Excellence through the FEDSTRIP/ MILSTRIP DLA Compressed Gases overarching initiative. Stringent specifications include product integrity, cylinder dimensions, DOT cylinder rating, PROP OF US GOVT stamping, valve specifications, cylinder indication and markings. By paralleling the DLA Compressed Gases program, commands can seamlessly exchange cylinders without incurring additional costs to the program.

Expedited Shipment?



National Shipments: FedEx Express

Deployment? Inspection? We have partnered with FedEx Express and obtained our IATA certification to ship 20#, 30# & 43# refrigerant cylinders from coast-to-coast in less than 24 hours. If the order is placed prior to 12:00pm the previous day, your order will arrive by 12:00pm the following day. Shipping & handling charges apply and are based on a case-by-case basis.



International Shipments: DHL Worldwide

Logistics issues abroad? We have Partnered with DHL Worldwide to ship refrigerant worldwide. Logistics, shipping & handling charges apply and are based on a case-by-case basis.



EPA §608/ 609 Technician Certification Verification Required

Military Commands Exempt

EPA Class I Refrigerant. EPA Certification is required to purchase this product. Purchaser must have been certified in accordance with EPA Regulation 40 CFR § 82 Subpart F or Subpart B (Section 608, HVAC). A copy of this certification must be provided prior to concluding sale.