

COMPRESSED CYLINDER SERVICES

Customer Service  
 T: (800) 610-4571  
 F: (800) 610-4571  
 customerservice@compcylserv.com  
 www.compcylserv.com



Deployment Now? 24/7 Dial X119




**R-236FA Refrigerant (Military)**  
**1,1,1,3,3,3-Hexafluoropropane**

Shipping Name: Liquefied gas, N.O.S. 1,1,1,3,3,3-Hexafluoropropane  
 UN3163  
 Hazard Class: 2.2 (Non-Flammable Gas)  
 CAS: 690-39-1  
 ERG: 126



e-Gas  
 CLICK HERE



CLICK HERE FOR MSDS

Synonyms: FE-36™; FE 36™; HFC-236fa; FC-236fa; CCO610; HCFC 236fa; R 236fa; 2,2-dihydroperfluoropropane; bistrifluoromethylmethane  
 ODP: 0 / GWP: 6300  
 AHSRAE Rating A1  
 Recommended Lubricant: POE Polyolester Oil  
 EPA SNAP Class I R-114 Replacement

**PURITY IS A PROBLEM! CERTIFIED PRODUCT ONLY: US NAVY FLEET**

**PURITY PROBLEM SOLVED = COMPCYLSERV**


Problem solved with COMPCYLSERV; we are one of only three companies globally whom can provide certified R-236FA to AHRI-700 (2011) Specifications & Military Standards. Among other requirements, the AHRI-2011 specification requires Halogenated Unsaturated Volatile Impurities <40ppm PPM By Weight, an unmatched industry challenge that has plagued manufacturers, suppliers & the Fleet. Knowledge is power. We provide a COA Certificate of Analysis from an independent EPA-Certified Facility with each cylinder at no additional charge.

**WHY DOES THIS MATTER?**

Product that does not meet the AHRI-700 (2011) specifications negates manufacturer liability/ warranty. Bad product also costs the Warfighter... Furthermore in large volumes Halogenated Unsaturated Compound Impurities can cause internal corrosion. There have also been traces of R-40 (Methyl Chloride or Chloromethane) identified in various refrigerants which is extremely toxic, flammable & highly reactive when exposed to aluminum. Know your product before installing aboard your centrifugal air conditioning unit.


**Valve Types**

DOT 4BW300 Refillable Cylinders  
 Dual Port/ Dual Valve Vapor & Liquid  
 NSN: 8120-01-204-0182  
 Connection: CGA-660




**STANDARD CYLINDER SIZES**

Cylinders shown are provided for reference only, all cylinders shall comply to color specifications as stated in MIL-STD-101B.



**MIL-STD-147E Palletization Available Upon Request**



**FEDSPEC Primary Color 12246 MIL-STD-101B & FED-STD-595**  
**Commercial, HVAC, Automotive AHRI (2012) N PMS 424**

Type	Content Capacity	Content NSN	Cylinder NSN	DOT	Tare Weight	Valve NSN	Outlet	Cylinder Exchange Price Includes COA	Cylinder Price Content Sold Separately
Product Identification Number IAW CID A-A-58060									
AA58060-R236FAW68	150LB (12"x36")	6830-01-525-9381	8120-01-525-9001	4BA/W300	63LB	8120-01-204-0182	CGA-660	\$4,350.00	\$245.00
AA58060-R236FAW454	1000LB	N/A	N/A	4BA/W240/300	335LB	8120-01-316-2208	CGA-660	Call For Pricing	\$2,000.00

Pricing subject to change without notice, based on market volatility.



**DLA Cylinder Specifications**

The Defense Logistics Agency adheres to stringent specifications in order to provide Logistics Excellence through the FEDSTRIP/ MILSTRIP DLA Compressed Gases overarching initiative. Stringent specifications include product integrity, cylinder dimensions, DOT cylinder rating, PROP OF US GOVT stamping, valve specifications, cylinder indication and markings. By paralleling the DLA Compressed Gases program, commands can seamlessly exchange cylinders without incurring additional costs to the program.

**Expedited Shipment?**



**National Shipments: FedEx Express**

Deployment? Inspection? We have partnered with FedEx Express and obtained our IATA certification to ship 20#, 30# & 43# refrigerant cylinders from coast-to-coast in less than 24 hours. If the order is placed prior to 12:00pm the previous day, your order will arrive by 12:00pm the following day. Shipping & handling charges apply and are based on a case-by-case basis.



**International Shipments: DHL Worldwide**

Logistics issues abroad? We have Partnered with DHL Worldwide to ship refrigerant worldwide. Logistics, shipping & handling charges apply and are based on a case-by-case basis.



**EPA §608/ 609 Technician Certification Verification Required**

Military Commands Exempt

EPA Class I Refrigerant. EPA Certification is required to purchase this product. Purchaser must have been certified in accordance with EPA Regulation 40 CFR § 82 Subpart F or Subpart B (Section 608, HVAC). A copy of this certification must be provided prior to concluding sale.